

Technical Data Sheet Touch-Up Spray 1C



Lacquering and touch-up for anodized aluminium

1-component acrylic lacquer in an aerosol can. Suitable for local colour correction and small repairs on anodized aluminium surfaces. Available in Alumat colours and transparent.

Technical Properties

- Good adhesion on anodized aluminium after proper surface preparation
- Coverage: 0.7–1 m² per spray can at 25–30 µ dry film thickness
- Fast drying
- Non-yellowing
- High covering power
- Dust dry: approx. 10 minutes
- Handle dry: approx. 30 minutes
- Fully cured: approx. 2 hours
- Scratch resistant
- Professional use
- Shelf life: 3 years (unopened packaging)
- Store according to the general requirements for aerosol cans. Protect from frost, humidity and heat
- Flammable

Use

- Surfaces must be clean and free of contaminants.
- Degrease the anodized aluminium surface with Etching Promotor before application.
- Shake the spray can 2–3 minutes before use.
- Spray from a distance of 20–25 cm.
- Apply several thin wet coats until the desired colour coverage is reached.
- The spray can contains two nozzles: 1 flat jet and 1 round jet.
- Avoid use below 15 °C and in extreme heat or high humidity.
- To extend the storage life after use: hold the spray can upside down and spray until no lacquer comes out. Store upside down afterwards.

Package

- 400 ml spray can